

[

IN THE CLAIMS:

1. (Currently Amended) An air purification system for receiving incoming air containing impurities and outputting purified air into ductwork of a building, the system comprising:

a hood defining a hood outlet in communication with the ductwork;

a primary filter member mounted to the hood for receiving the incoming air, removing at least a portion of the impurities therefrom, and outputting a primary airflow; and

a secondary filter member mounted to the hood at a location downstream of the primary filter for receiving the primary output airflow therefrom, the secondary filter member having a secondary filter beads media selected from the group consisting of silica, metal, glass, a diatomaceous earth, and zeolite, wherein the beads are operable to remove impurities from the primary airflow and output a secondary airflow to the hood outlet that is cleaner than the primary airflow.

2. (Original) The air purification system as recited in claim 1, further comprising a duct collar connected between the hood outlet and the ductwork to receive the secondary airflow from the secondary filter and forward the secondary airflow to the ductwork.

3. (Original) The air purification system as recited in claim 1, wherein the primary air filter operates using centrifugal filtration principles.

4. (Original) The air purification system as recited in claim 3, further comprising a collector disposed at one end of the primary filter operable to receive impurities removed from the incoming air.

5. (Currently Amended) The air purification system as recited in claim 1, wherein the bed further comprises ~~secondary air filter includes~~ inner and outer porous walls ~~defining a bed therebetween~~ packed with the beads ~~a filter media operable~~ to trap therein the impurities removed from the primary airflow.

6. (Currently Amended) The air purification system as recited in claim 1 ~~5~~, wherein the beads are ~~filter media is~~ porous.

7. (Currently Amended) The air purification system as recited in claim 1 6, wherein the ~~porous media comprises a silica gel~~ beads are nonporous.

8. (Currently Amended) The air purification system as recited in claim 1 5, wherein the secondary air filter is operable to collect grease particles and VOC's.

9. (Currently Amended) The air purification system as recited in claim 7 5, wherein the beads ~~filter media is nonporous and defines~~ define gaps therebetween that are sized to store the additional impurities therein.

10. (Original) The air purification system as recited in claim 9, further comprising a collector disposed at one end of the secondary filter member operable to receive the additional particles therefrom.

11. (Currently Amended) The air purification system as recited in claim 7 9, wherein the ~~nonporous beads are~~ media is selected from the group consisting of a glass and metal.

12. (Original) The air purification system as recited in claim 5, further comprising a removable outer wall that encloses the bed.

13. (Original) The air purification system as recited in claim 1, further comprising a fan operable to draw air through the primary and secondary filter members and out the duct collar.

14. (Original) The air purification system as recited in claim 3, wherein the primary filter member further comprises:

an elongated air filter chamber having a closed front, rear and closed opposing ends;
a pair of inlets formed in said air filter chamber front, each inlet of said pair of inlets being located adjacent one of said air filter chamber ends; and

an outlet formed in said chamber rear and located substantially midway between the opposing ends, wherein air enters said air filter chamber through said inlets and flows longitudinally toward said outlet through said air filter chamber in a helical path, wherein said helical path causes impurities in said air to impinge upon walls of said air filter chamber prior to said air exiting said air filter chamber through said outlet.

~~14~~ ¹³ (Currently Amended) The air purification system as recited in claim 1, wherein the secondary filter member further comprises at least one chamber having a front face for receiving incoming air, wherein the chamber is defined by porous walls that contain ~~are packed with the beads a filter media~~, and wherein the porous walls extend outwardly from the front face.

~~18~~ ¹⁶ (Original) An air filter chamber comprising:
a top wall;
a pair of side walls extending inwardly from outer ends of the top wall at one end and having distal ends at an opposite end; and
a front face defined by distal ends of the side walls configured to receive incoming impure air and direct the air into the top wall and side walls;

wherein the top and side walls are defined by inner and outer porous members enclosing a filter media therein; and

wherein the side walls extend substantially perpendicularly outwardly from the front face.

~~19~~ ¹⁷ (Original) The air filter chamber as recited in claim ~~16~~ ¹⁸, wherein the inner and outer porous members are spaced apart by a distance less than one inch.

~~20~~ ¹⁸ (Original) The air filter chamber as recited in claim ~~16~~ ¹⁸, wherein the inner and outer porous members are spaced apart at a distance which does not allow a pressure drop greater than 2 in H₂O.

~~21~~ ¹⁸ (Original) The air filter chamber as recited in claim ~~16~~ ¹⁸, wherein the filter media comprises a porous material.

~~22~~ ²¹ (Original) The air filter chamber as recited in claim ~~16~~ ²¹, wherein the filter media comprises a silica gel.

~~23~~ ²¹ (Original) The air filter chamber as recited in claim ~~16~~ ²¹, wherein the filter media comprises a ceramic.

~~24~~ ¹⁸ (Original) The air filter chamber as recited in claim ~~16~~ ¹⁸, wherein the filter media comprises a nonporous material.

~~25~~²⁴ 23. (Original) The air filter chamber as recited in claim 22, wherein the filter media is selected from the group consisting of glass and metal.

~~26~~¹⁸ 24. (Original) The air filter chamber as recited in claim 16, further comprising a pair of end walls disposed at distal ends of the inner and outer porous members to seal the filter media therein.

~~27~~²⁶ 25. (Original) The air filter chamber as recited in claim 24, wherein at least one of the end walls is removable.

~~28~~ 26. (Currently Amended) A method of removing impurities from an airflow in an air purification system disposed upstream of a building's ductwork, the air purification system being of the type having a primary filter and a secondary filter, the steps comprising:

(A) drawing incoming air having air impurities into the primary filter;

(B) removing air particles from the incoming airflow at the primary filter to produce a primary airflow;

(C) outputting the primary airflow directly into a filter media of ~~to the~~ secondary filter that includes filtering beads;

(D) removing air particles from the primary airflow at the secondary filter media to produce a secondary airflow; and

(E) outputting the secondary airflow into the ductwork.

~~29~~²⁸ 27. (Original) The method as recited in claim 26, wherein step (B) further comprises subjecting the incoming air to centrifugal forces.

~~30~~²⁸ 28. (Currently Amended) The method as recited in claim 26, wherein the filtering beads are arranged as a packed bed of beads in the secondary filter ~~step (D) further comprises the step of directing the primary airflow into a packed bed of filter media.~~

~~31~~²⁸ 29. (Currently Amended) The method as recited in claim 26, wherein the ~~filter media comprises a plurality of~~ filtering beads are porous beads, wherein step (D) further comprises the step of absorbing impurities from the primary airflow into the beads.

~~32~~³¹ 30. (Currently Amended) The method as recited in claim 29, wherein the porous beads are made of ~~a~~-silica gel.

31. (Currently Amended) The method as recited in claim ~~26~~ ²⁸ 28, wherein the ~~filter media comprises a plurality of nonporous beads~~ define defining air gaps therebetween, and wherein step (D) further comprises the step of absorbing impurities from the primary airflow into the air gaps.

32. (Currently Amended) The method as recited in claim ~~31~~ ³³ 31, wherein the ~~nonporous~~ beads are nonporous and selected from the group consisting of glass and metal.

33. (Currently Amended) In an air purification system for removing airborne particles from an airflow prior to emitting the airflow into a buildings ductwork, the system including a hood defining a space for receiving incoming air having impurities and an outlet connected to the ductwork, and a primary filter mounted to the hood within the space, wherein the primary filter receives the incoming air and removes impurities prior to outputting once-filtered air towards the outlet, the improvement comprising:

91
cont. a secondary filter mounted within the hood and disposed within the space at a location downstream of the primary filter, the secondary filter including a bed of filtering beads ~~operable to receive~~ that receives the once-filtered air from the primary filter and ~~further remove~~ entraps airborne particles to output at least twice-filtered air towards the outlet.

40 34. (Original) The improvement as recited in claim ~~33~~ ³⁹ 33, wherein the primary and secondary filters are angularly mounted within the hood.

53 35. (Currently Amended) A method of fabricating a two stage air purification system operable to receive incoming air having air impurities and outputting twice filtered air into the ductwork of a building, the steps comprising:

providing a hood defining a hood outlet that is connectable to the ductwork, wherein the hood has a first filter mounted thereto to receive the incoming air and output once-filtered air toward the outlet; and

mounting a second filter to the hood at a location downstream of the first filter to receive the once-filtered air and output the twice-filtered air toward the hood outlet, wherein the second filter has a filter media including filter beads, and wherein air can pass from the first filter to the second filter without passing through any other air filters.

~~15~~ ~~36~~ (New) The air purification system as recited in claim 1, wherein the silica is a silica gel.

~~16~~ ~~37~~ (New) The air purification system as recited in claim 1, wherein the primary filter is a baffle filter.

~~17~~ ~~38~~ (New) The air purification system as recited in claim 1, wherein air output from the primary filter does not pass through a filter media prior to entering the secondary filter member.

~~35~~ ~~39~~ (New) The air purification system as recited in claim ~~26~~²⁸, wherein the beads are selected from the group consisting of silica, metal, and glass.

~~36~~ ~~40~~ (New) The air purification system as recited in claim ~~39~~³⁵, wherein the silica is a silica gel.

~~37~~ ~~41~~ (New) The method as recited in claim ~~28~~²⁸, wherein the secondary airflow is output directly from the secondary filter into the ductwork without passing through an additional filter.

~~38~~ ~~42~~ (New) The method as recited in claim ~~31~~³³, wherein the beads are nonporous.

~~49~~ ~~43~~ (New) An air purification system for receiving incoming air containing impurities and outputting purified air into ductwork of a building, the system comprising:

a hood defining a hood outlet in communication with the ductwork;

a primary filter member mounted to the hood for receiving the incoming air, removing at least a portion of the impurities therefrom, and outputting a primary airflow; and

a secondary filter member mounted to the hood at a location downstream of the primary filter for receiving the primary output airflow therefrom, the secondary filter member having an inner and outer porous walls defining a bed packed with secondary filter media operable to remove impurities from the primary airflow and trap therein the removed impurities and output a secondary airflow to the hood outlet that is cleaner than the primary airflow,

wherein the filter media is nonporous and defines define gaps therebetween that are sized to entrap the additional impurities therein.

~~50~~ ~~44~~ (New) The air purification system as recited in claim ~~43~~⁴⁹, further comprising a collector disposed at one end of the secondary filter member operable to receive the additional particles therefrom.

~~51~~ ~~45~~ (New) The air purification system as recited in claim ~~43~~⁴⁹, wherein the nonporous media is selected from the group consisting of a glass and metal.

~~52~~ ~~46~~ (New) The air purification system as recited in claim ~~43~~⁴⁹, further comprising a removable outer wall that encloses the bed.

~~48~~ ~~47~~ (New) The air purification system as recited in claim ~~33~~³⁹, wherein the bed of beads is packed.

~~41~~ ~~48~~ (New) The air purification system as recited in claim ~~33~~³⁹, wherein the secondary filter further comprises a wall that opens to enable the bed of beads to be removed from the filter.

A1
cont. ~~42~~ ~~49~~ (New) The air purification system as recited in claim ~~33~~³⁹, wherein the beads are porous.

~~43~~ ~~50~~ (New) The air purification system as recited in claim ~~33~~³⁹, wherein the beads are nonporous.

~~44~~ ~~51~~ (New) The air purification system as recited in claim ~~33~~³⁹, wherein the secondary filter is disposed immediately downstream of the primary filter.

~~45~~ ~~52~~ (New) The air purification system as recited in claim ~~33~~³⁹, wherein the beads are selected from the group consisting of silica, metal, glass, a diatomaceous earth, and zeolite.

~~46~~ ~~53~~ (New) The air purification system as recited in claim ~~33~~³⁹, wherein the airborne particles are organic.

~~47~~ ~~54~~ (New) The air purification system as recited in claim ~~33~~³⁹, wherein the airborne particles comprise grease.